






FIG. 12

































FIG. 25(b)










FIG. 28








F1G. 31





422 /HO Output 546 527 545 54 Hori LPF Hori HPF **54** 541 Oversampler HHV. 526 r 525 H:WH (土) 智慧 739 739 H Y 524 2nd video decoder Ver.HPF Ver.LPF Ver.HPF Ver.LPF 523 537 535 3rd 533 Servander Oversampler expander Oversampler → Oversampler Oversampler 2nd 532 expander 522 1st expander 45 ... 왕 D₂ 2 2nd input Di 15t input


554 , 233 오 **HHVF2** 552 , 55 , 242 742 Hori HPF Hori LPF Oversampl ₹, 분 \pm 돌 H.Y 3rd video decoder 524 538 Super-high band video decoder Ver.LPF Ver.HPF Ver.HPF Ver.LPF 537, 535 Oversampler Oversampler Oversampler - Oversampler 523 2nd 532 expander 1st : expander ## | ## 531 Divider 551 539 27 D3 13 3rd input D2 12 2nd input Di 计 1st input

1













452i 452h 522b 491b 0,4% 452g 521b တ 522a 491a O₁+; Ť 452d 452e 452f 521a <u>က</u> 491 FIG. 42 ద్ ద్ ద్ 522 Frame S 521 S | D1 | D2 | D3 | D4 | S | 10 | D1 | D2 | D3 505 <u>o</u> = S1 S2 S3 51 52 52 452 452a 452b


FIG. 43











•

.....

			1	Ť.		<u> </u>	<u> </u>			<u></u>
	750e 6	,721e	9 .	M6		H6-1	H6-2		H6-3	S H6-4
	-	741e	S	S		S	S	[8	
	750d	7210	L.5	M5		H5-1	H5-2			H5-4
	0	7410	<u>σ</u>	<u></u>		S	S		හ <u></u>	
	750c	° 721c	۲4	M4		H4-1	S H4-2		S H4-3	S H4-4
	g -	741c	S	S		<u>o</u>			H3-3	H3-4
⊢ 	3 / 55	741b 731b //721b	L3	. W	•	S H3-1	S H3-2		S H	<u>8</u>
	750a	B	S	M2	*******	H2-1	H2-2		H2-3	H2-4
	6	741a 731a	s L2	Σ <u>σ</u>		T S	T S		<u>N</u>	<u> </u>
	750	7 7	1			<u>-</u>	1-2		11-3	H1-4
	7	731 7		\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \		S H1	S H		I S	S
	, -	720 741	- s	S	·	<u>σ</u>	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \		S	S
 9	l		2	H O		O ^2	O H2		0	유






FIG. 52



F1G. 54

FIG. 55








FIG. 61









FIG. 66






FIG. 72

FIG. 73

	-				
	[,		±= 1 → ±=
					‡
					tr1 tr2
Н-и/н-Н					Ξ
			2		t10
H _H V _L -H			Timing 2		់ ខា
					ta 8
H _L V _H -H					4
工					† 6
		·			<u>.</u>
					4
		를 			t3
		HH/L	Timing		- 2]
		Н. Ин Нн			سنه
		D1 HKVL			.=
~~~	1	-	4		<u>.</u> e




FIG. 75




FIG. 76







FIG. 77




**t**ts 823b H-H/H-H <u>‡</u> Ŧ 823a 王-关5 12 Ξ. 823 H-\H (E) <u>\$</u> FIG. 79 **₽ ₽** 上計(1) 821c 45 عـ [HHV(1) 821b **₽ =** 821a **-**5 **₽** D, HW(1) 821 Õ 








554 Outpu 765a Switch 556 Mixer НнVн HLVH HHVL HLVL Switch 7 7.65 Video encoder 812a Switch 503 Expander 530 Input  $\tilde{\Box}$ 





855 854 000 , 833 857a 857b 858a Recording/playback 958 858b 858 858 reproduction generator Carrier circuit bias 富 Magnetic recording/playback apparatus 852 **8** carrier - C-CDM demodulator /demodulator 99 C-CDM modulator circuit Modulator 2nd data stream output 759b 401b 2nd data stream input 744b 759 757 747 743 758 ist data stream output 1st data stream input Trellis Decoder Encoder 743a Output section 1/4/40 Trailis 758a Input section ည္သ ပ္သ 759a ည္သ 40_{la} 705 8 →2nd video encoder-→lst video encoder-402a 402b ist video decoder 2nd video decoder Video encoder Video decoder (VTGS) (HDTV) (VTQH) |-






















548c g Video mixer 33 - HLVH Н Н Н HHVL H/L 531c N က Divider 1 H-HVHH Video mixer 548b F1G. 94 Video signal mixer Video mixer HHVH out out H_VH H.VH 고 사 포 Mixer H 光 H.Vr 531a 531b Divider 1 Divider 1 .⊑ 王 王 로 523b 5230 5234 02-1










FIG. 100



Pe



Pe




FIG. 103




FIG. 104






FIG. 106



130 140 150 160 170 712 gradeB 36-SRQAM(D1-1) 65.8miles (Hybrid SRQAM) S6miles NTSC 1200' HAAT 90 100 110 120 37dBk Interference Contour 30dB Receiver C/I 36-SRQAM(D1.2) 59.8miles 36-SRQAM(D2) 47.8miles SRQAM(S1=1.8) 41.5miles* Distance from transmitting antenna [miles] S 5 -115miles-FIG. 107 50 60 20dB C/N SdB C/N 10dB C/N <del>수</del> 45 miles* 6SRQAM 42 miles** 36SRQAM 53 miles** 36SRQAM 56 miles** 701 50 miles* 33 20 ,703b Digital TV 1200'HAAT 22.5dBk ,03c 56.8 miles 16-QAM ā <u>7</u> 52 miles 36-QAM. ឧ 20 10 47.8miles 59.8 miles 2 55.8 miles 12.5dB C/N 16-QAM 56.8miles. 16.5dB C/N 36-QAM 52miles 50 40 Standard QAM 8 (miles)

* *: approximately calculated








FIG. 111









FIG. 114





Microphone Speaker 503 D2 Compressor 405 Expander 8 õ ဝ õ 99/ 767 CPTime division 765 Timing circuit BaimiT ឧ 8 පි õõ Demodulator Modulator 764 sharing unit Antenna

763

FIG. 115

Ţ












FIG. 123








| Received | Signal 품 4 UP Convertor Convertor Input cir Down Tabivid Summer 45b 450 Demodulator C-CDM Demodulator Modulator C-CDM Demod. C-CDM Modulator C-CDM Demod. C-CDM Damod. C-CDM Demod C-CDM Mod. C-CDM Mod. C-CDM Mod. C-CDM Mod. 791 FIG. 127 Transmitter Parallel to Serial Convertor Receiver Serial to Parallel Convertor 338 757 ō õ 402b ata stream output 7436 Normal Gain 401b and data stream input 402c 1st data stream outs MOT MOT Trellis Encoder Output section Input section 0.5 401c ist data stream Nomal gain ECC High gain ECC High Gain ည္မ င္ပင္ 744a 7581 \$<del>\\$</del> PZ07 <u> 3/3</u> PLOT 1st video decoder 1-2 video decoder 2nd video decodei 1-2 video encoder 1st video encoder -1 video decoder 2nd video encoder -1 video encoder Video decoder Video encoder (∨TOJ) <del>|<₁>|</del> HDTV ) (VTQH)





GHOST DELAY - 2us. D/U - 8dB FIG. 130








FIG. 131











HDTV: 15.20Mbps EDTV: 8Mbps SDTV: 4Mbps LDTV: 1.15Mbps +60.1% (S=2.5)(16QAM) 36-SRQAM (S=1.8) 32-QAM FIG. 135 -15.4%) .....(S=2.5) (or SDTV X2) Extended 10Mbps 20 20 39 100Mbps

Receiver-2 Redundancy for FEC Hybrid 36-SRQAM 5000 (+34.2%) Subchannel-1-1 4000 (+10.8%)Coverage Area (square miles) 3000 2000 1000 1Mbps 0.5 n Transfer Rate (Mbps)

Е-тэуізээЯ





## This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

| BLACK BORDERS
| IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
| FADED TEXT OR DRAWING
| BLURRED OR ILLEGIBLE TEXT OR DRAWING
| SKEWED/SLANTED IMAGES
| COLOR OR BLACK AND WHITE PHOTOGRAPHS
| GRAY SCALE DOCUMENTS
| LINES OR MARKS ON ORIGINAL DOCUMENT
| REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

## IMAGES ARE BEST AVAILABLE COPY.

☐ OTHER:

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.